


TOTAL POWER INTERNATIONAL, INC.

NEW PC 104 POWER SUPPLY

TP-DMP-0070 PC 104 Power Supply

FEATURES

PC104 Format



SPECIFICATIONS

INPUT

Input Voltage:	850264VAC, Universal
Input Frequency:	47 - 63 Hz.
Input Connector:	Molex.
Inrush Current:	20A @ 110VAC. 40A @ 220VAC.
EMI/RFI:	EN55022 Class B.
Hold-Up Time:	16ms @ 110VAC.
Safety Approvals:	UL, cUL, TUV, Tmark CE
Weight:	90Gm
Size:	3.55" x 3.77" x 0.43"

OUTPUT

Output Wattage:	26.6 Watts.
Line Regulation:	±0.1% typ.
Load Regulation:	±2.0% for 5V typ. ±5.0% for 12V typ. ±10% for -5V typ. ±10% for -12V typ.
Noise & Ripple:	1% P-P typ.
OVP:	125% ±5%.
Short Circuit Protection:	Auto-recovery.
Output Connector:	PC104 Format.
Operating Temp:	-20C - +50C.

OUTPUT VOLTAGE / CURRENT RATING CHARTS

SINGLE OUTPUT

MODEL NUMBER	OUTPUT
TPDMP-0070	+5V / 0.4-2.0A
	-5V / 0-0.2A
	+12V / 0-1.0A
	-12V / 0-0.2A

THREE EASY STEPS TO OBTAIN A SAMPLE OR PLACE AN ORDER.

- 1.) PRINT OUT THIS PDF DATA SHEET AND DETERMINE MODEL NEEDED.
- 2.) FILL OUT QUICK QUOTE REQUEST FORM. TPI WILL QUICKLY E-MAIL YOU THE COST OF SAMPLE OR QUANTITY YOU REQUESTED.
3.) ONCE YOU RECEIVE OUR QUOTE, YOU CAN FILL OUT AN ORDER FORM ON OUR WEBSITE AT WWW.TOTAL-POWER.COM OR CALL OUR TOLL FREE HOT LINE NUMBER TO PLACE YOUR ORDER.

1-877-646-0900