

TOTAL POWER INT'L TPSPU65 SERIES

80W Desk Top Switching Power Supplies For I.T.E.

Description:

The TPSPU65 series of AC/DC switching mode power supplies provide 80 Watts of continuous output power.

All supplies are UL 94V-0 compliant, include IEC-320-C input for worldwide applications. All models meet FCC Pa 15 class B and CISPR-22 class B emission Limits and are designed to comply with UL, C-UL, TUV and CE requirements. All units are 100% burned in and tested.



Features:

- Wide Input Voltage 90 to 264 VAC, 47 to 63 Hz
- IEC-320-C14 Input Inlet
- Single to Quad Output
- Output Voltage Available From 3 VDC Thru 48 VDC
- Optional Output Connector (See appendix)
- Input Surge Current, Over Voltage and Over Load protection
- Splash proof
- One Year Warranty

Safety Approvals :



Electrical Characteristics:

Sym.	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Vin	Input Voltage		90		264	VAC
Fin	Input Frequency		47		63	Hz
Wo	Output Power Range	Vin=90 to 264VAC	0		80	W
Vo	Output Voltage Range		See rating chart			V
Io	Output Current Range		See rating chart			A
Iil	Input Current (Low Line)	Io=Full load, Vin=115VAC			1.9	A
Iih	Input Current (High Line)	Io=Full load, Vin=230 VAC			1.5	A
Irl	Low Line Inrush Current	Io=Full load, 25 c, Cool start, Vin=115VAC		12	15	A
Irh	High Line Inrush Current	Io=Full load, 25 c, Cool start, Vin=230VAC		26	30	A
Eff	Efficiency	Io=Full Load, Vin=230VAC	75	83	88	%
REG-i	Line Regulation	Io=Full Load		0.5	1	%
REG-o	Load Regulation	Vin=230VAC		3	7	%
OVP	Over Voltage Protection		112		132	%
OCP	Over Current Protection		110		150	%
Ttr	Transient Response	Io=Full Load to Half Load, Vin=100VAC			4	mS
Thold	Hold-Up Time	Io=Full Load, Vin=100VAC	16			mS
Ts	Start Up Time	Io=Full Load, Vin=100VAC	0.3	1	2	S
Vrn	Ripple & Noise (Peak to Peak)	Full Load, Vin=90VAC		1	2	%
Ilk	Safety Ground Leakage Current	Io=Full Load, Vin=240VAC		0.5	0.75	mA
Tc	Temperature Coefficient	All output	-0.04		0.04	%/ c

Environmental :

Sym.	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Toper	Operating Temperature		0		70	c
Tstg	Storage Temperature		-40		85	c
Hr	Relative Humidity		5		95	%
Pd	Derate linearly from 100% load at 40 c to 50% load at 70 c					

Safety Specifications:

Sym.	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Vps	Dielectric Withstanding Voltage for Primary to secondary	Primary to secondary	4242			VDC
Vpg	Dielectric Withstanding Voltage for Primary to ground	Primary to ground	2121			VDC
Ri	Isolation Resistance	Test Voltage = 500VDC	50			MΩ
CISPR	EMI requirements for CISPR-22	Vin=220VAC	B			CLASS
FCC	EMI requirements for FCC PART-15	Vin=110VAC	B			CLASS


TOTAL POWER INT'L TPSPU65 SERIES

80W Desk Top Switching Power Supplies For I.T.E.

Output Voltage And Current Rating Chart (Single Output) :

Model Number	Output Voltage	Output Current	Total Regulation	Maximum Output Power
TPSPU65-101	3 ~ 5 VDC	16.6 ~ 10.0 A	7%	50W
TPSPU65-102	5 ~ 6 VDC	13.0 ~ 10.8 A	7%	65W
TPSPU65-103	6 ~ 8 VDC	11.6 ~ 8.70 A	5%	69.6W
TPSPU65-104	8 ~ 11 VDC	9.37 ~ 6.81 A	5%	75W
TPSPU65-105	11 ~ 13 VDC	7.27 ~ 6.15 A	5%	80W
TPSPU65-106	13 ~ 16 VDC	6.15 ~ 5.00 A	5%	80W
TPSPU65-107	16 ~ 21 VDC	5.00 ~ 3.80 A	5%	80W
TPSPU65-108	21 ~ 27 VDC	3.80 ~ 2.96 A	5%	80W
TPSPU65-109	27 ~ 33 VDC	2.96 ~ 2.42 A	5%	80W
TPSPU65-110	33 ~ 40 VDC	2.42 ~ 2.00 A	5%	80W
TPSPU65-111	40 ~ 48 VDC	2.00 ~ 1.66 A	5%	80W

Mechanical Specifications :



Note:

1. Dimensions are shown in mm.
2. Weight: 570-750gs approx.
3. Optional output connector: See page Appendix.